



## C8/80/15

C8/80/15 was originally designed as a pig fence, but now is widely used as a general all-purpose fence. This fence is ministry grant approved.

Mild steel stock fence does not need to be strained as tight as high tensile products. This means it is particularly useful if you have lots of turns in your fence as gradual turns can be made off intermediate posts.

|                                 |                                |
|---------------------------------|--------------------------------|
| Line wires                      | 8                              |
| Distance between vertical wires | 15cm                           |
| Height                          | 80cm                           |
| Top and bottom line wires       | 3.00mm - 695 N/mm <sup>2</sup> |
| Intermediate line wires         | 2.5mm - 695 N/mm <sup>2</sup>  |
| Vertical wires                  | 2.5mm - 415 N/mm <sup>2</sup>  |
| Roll lengths available          | 50m, 100m, 250m                |
| Weight of 50m roll              | 32kg                           |

| SPACING BETWEEN SUCCESSIONAL HORIZONTAL WIRES FROM THE TOP | 8 / 80 / 15<br>-----150mm-----<br>-----6"-----<br>VERTICAL SPACING |
|------------------------------------------------------------|--------------------------------------------------------------------|
| 152mm                                                      |                                                                    |
| 140mm                                                      |                                                                    |
| 131mm                                                      |                                                                    |
| 114mm                                                      |                                                                    |
| 102mm                                                      |                                                                    |
| 83mm                                                       |                                                                    |
| 83mm                                                       |                                                                    |



Manufactured to BS EN 10223. Galvanised to BS EN 10244 Class A